

# The Current Object



Up to now, we have tacitly ignored the trailing parameter of type `Ice::Current` that is passed to each skeleton operation on the server side. The `Current` structure is defined as follows:

## Slice

```
module Ice
{
    local dictionary<string, string> Context;

    enum OperationMode { Normal, \Idempotent }

    local struct Current
    {
        ObjectAdapter    adapter;
        Connection        con;
        Identity          id;
        string            facet;
        string            operation;
        OperationMode     mode;
        Context           ctx;
        int               requestId;
        EncodingVersion   encoding;
    }
}
```

Note that the `Current` value provides access to information about the currently executing request to the implementation of an operation in the server:

- `adapter`  
The `adapter` member provides access to the object adapter via which the request is being dispatched. In turn, the adapter provides access to its communicator (via the [getCommunicator](#) operation).
- `con`  
The `con` member provides information about the [connection](#) over which this request was received.
- `id`  
The `id` member provides the [object identity](#) for the current request.
- `facet`  
The `facet` member provides access to the [facet](#) for the request.
- `operation`  
The `operation` member contains the name of the operation that is being invoked. Note that the operation name may indicate one of the [operations on Ice::Object](#), such as `ice_ping` or `ice_isA`. (`ice_isA` is invoked if a client performs a `checkedCast`.)
- `mode`  
The `mode` member contains the invocation mode for the operation (`Normal` or `Idempotent`), which influences the [retry behavior](#) of the Ice run time.
- `ctx`  
The `ctx` member contains the current [request context](#) for the invocation.
- `requestId`  
The Ice [protocol](#) uses request IDs to associate replies with their corresponding requests. The `requestId` member provides this ID. For oneway requests (which do not have replies), the request ID is 0. For collocated requests (which do not use the Ice protocol), the request ID is -1.
- `encoding`  
The [encoding](#) version used to encode the input and output parameters.

If you implement your server such that it uses a separate servant for each Ice object, the contents of `Current` are not particularly interesting. (You would most likely access `Current` to read the `adapter` member, for example, to activate or deactivate a servant.) However, as we will see in our discussion of [default servants](#) and [servant locators](#), the `Current` object is essential for more sophisticated (and more scalable) servant implementations.

[Back to Top](#) ^

See Also

- [Object Identity](#)
- [Default Servants](#)
- [Servant Locators](#)
- [Request Contexts](#)
- [Versioning](#)
- [Using Connections](#)
- [The Ice Protocol](#)

