

Slice2Java Ant Task

On this page:

- [Execution Environment](#)
- [Dependencies](#)
- [Parameters](#)
- [Nested Elements](#)
- [Using the Task](#)

Ice for Java includes an ant task named `Slice2JavaTask` that automates the execution of the Slice-to-Java compiler. The task and its supporting classes reside in the JAR file named `ant-ice.jar`, which normally can be found in the `lib` subdirectory of your Ice installation.

Execution Environment

The `Slice2JavaTask` must be able to locate and spawn the `slice2java` executable. You can specify the directory of your Ice installation by defining the `ice.home` ant property or the `ICE_HOME` environment variable, in which case the task assumes that the Slice compiler's executable is located in the `bin` subdirectory of the specified installation directory. For example, if `ICE_HOME` is set to `/opt/Ice` on Linux, the task assumes that the executable path name is `/opt/Ice/bin/slice2java`. Furthermore, the task also configures its shared library search path (if necessary for your platform) to ensure the executable can resolve its library dependencies.

If both `ice.home` and `ICE_HOME` are defined, `ice.home` takes precedence. If neither are defined, the task assumes that the executable can already be found in your `PATH` and that your shared library search path is configured correctly.

Finally, you can use a task parameter to specify the full path name of the Slice compiler. Again, the task assumes that your shared library search path is configured correctly.

Dependencies

The task minimizes recompilation by maintaining dependencies between Slice files. The task stores this information in a file named `.depend` in the output directory and updates these dependencies after each invocation. (You can specify a different name for this file using a task parameter.)

Note that the task does not maintain dependencies between a Slice file and its generated Java source files. Consequently, removing the generated Java source files does not cause the task to recompile a Slice file. In fact, the task only compiles a Slice file when any of the following conditions are true:

- no dependency file exists
- no dependency information is found for the Slice file
- the modification time of the Slice file is later than the modification time of the dependency file
- the Slice file includes another Slice file that is eligible for compilation

The simplest way to force the task to recompile all of your Slice files is to remove the dependency file.

Parameters

The task supports the parameters listed in the following table:

Attribute	Description	Required
<code>checksum</code>	Specifies the name of a class to contain the Slice checksums .	No
<code>dependencyfile</code>	Specifies an alternate name for the dependency file. If you specify a relative filename, it is relative to ant's current working directory. If not specified, the task uses the name <code>.depend</code> by default. If you do not define this attribute and <code>outputdir</code> is defined, the task creates the <code>.depend</code> file in the designated output directory (see <code>outputdir</code>).	No
<code>ice</code>	Instructs the Slice compiler to permit symbols that have the reserved prefix <code>Ice</code> . This parameter is used in the Ice build system and is not normally required by applications.	No
<code>outputdir</code>	Specifies the directory in which the Slice compiler generates Java source files. If not specified, the task uses ant's current working directory.	No
<code>stream</code>	Indicates whether to generate streaming support . If not specified, streaming support is not generated.	No
<code>tie</code>	Indicates whether to generate tie classes . If not specified, tie classes are not generated.	No
<code>translator</code>	Specifies the path name of the Slice compiler. If not specified, the task locates the Slice compiler in its execution environment .	No

For the flag parameters (`ice`, `stream`, and `tie`), legal positive values are `on`, `true`, or `yes`; negative values are `off`, `false`, or `no`.

Nested Elements

Several Slice compiler options must be defined as nested elements of the task:

- `define`
Defines a preprocessor macro. The element supports the attributes `name` and (optionally) `value`, as shown below:

```
<define name="FOO">
<define name="BAR" value="5">
```

 These definitions are equivalent to the command-line options `-DFOO` and `-DBAR=5`, respectively.
- `fileset`
Specifies the set of Slice files to be compiled. Refer to the ant documentation of its `FileSet` type for more information.
- `includepath`
Specifies the include file search path for Slice files. In ant terminology, `includepath` is a *path-like structure*. Refer to the ant documentation of its `Path` type for more information.
- `meta`
Defines a global metadata directive in each Slice file as well as in each included Slice file. The element supports `name` and `value` attributes.

Using the Task

Define the following `taskdef` element in your project's build file to enable the task:

Ant

```
<taskdef name="slice2java" classname="Slice2JavaTask"/>
```

This configuration assumes that `ant-ice.jar` is already present in ant's class path. Alternatively, you can specify the JAR explicitly as follows:

Ant

```
<taskdef name="slice2java" classpath="/opt/Ice/lib/ant-ice.jar"
  classname="Slice2JavaTask"/>
```

Once activated, you can invoke the task to translate your Slice files. The example shown below is a simplified version of the ant project for the `hello` demo:

Ant

```

<target name="generate" depends="init">
  <mkdir dir="generated"/>
  <slice2java outputdir="generated">
    <fileset dir="." includes="Hello.ice"/>
  </slice2java>
</target>

<target name="compile" depends="generate">
  <mkdir dir="classes"/>
  <javac srcdir=".:generated" destdir="classes">
    <exclude name="generated/**"/>
    ...
  </javac>
</target>

<target name="all" depends="compile"/>

<target name="clean">
  <delete dir="generated"/>
  <delete dir="classes"/>
</target>

```

This project demonstrates some practices that we encourage you to adopt in your own projects. First, it is helpful to keep the source files generated by the Slice compiler separate from your application's source files by dedicating an output directory for the exclusive use of the Slice compiler. Doing so helps to minimize confusion and makes it easier to configure a source-code management system to ignore generated files.

Next, we also recommend that you include a `clean` target in your ant project that removes this output directory. Assuming that the dependency file (`.depend`) is also stored in this directory, removing the output directory is an efficient way to clean up your project's source tree and guarantees that all of your Slice files are recompiled in the next build.

Finally, after seeing the `exclude` element in the invocation of `javac` you might infer that the generated code was not being compiled, but the presence of the output directory in the `srcdir` attribute ensures that the generated code is included in the build. The purpose of the `exclude` element is to prevent ant from including the generated files twice in its target list.

See Also

- [slice2java Command-Line Options](#)
- [Using the Slice Compilers](#)
- [Using Slice Checksums in Java](#)
- [Tie Classes in Java](#)
- [Streaming Interfaces](#)